



Safe Lite Series

ATS Safe Lite Ultraviolet Disinfection Systems are an effective way to provide bacteria free water for your home or industry 24 hours a day, 7 days a week. Today's Ultraviolet Disinfection Systems are setting the standards for water disinfection requirements in the water treatment industry.





Features

- Standard warranty
- Completely automatic
- Compact & easy to install
- Low operating costs
- Low maintenance
- No taste or odor

Remove *what you can't see!*

- Eliminates microbiological contaminants without chemicals.
- Bacteria, viruses & other microbiological organisms are destroyed safely inside a factory sealed & tested chamber.



Aqua Treatment Service, Inc.
Providing Better Water For Better Living



Proudly Made
in the U.S.A.




Water
Quality
ASSOCIATION

Safe Lite Series

SPECIFICATIONS

Model #	Max. Flow GPM	No. Lamps	KW @ 120V	AMP @ 120V	Pipe Size	Overall Dimensions L x W x D	Wetted Material	Shipping Weight
SL-2V	2	1	0.03	0.25	3/8" MIP	15.5" x 5" x 5"	304 SS Tubing	7 Lbs.
SL-8V	8	1	0.03	0.25	3/4" MIP	21" x 5" x 5"	304 SS Tubing	8.5 Lbs.



1. Water enters the unit through the inlet port of the ultraviolet chamber.

2. The water flows through the chamber and swirls around a low pressure mercury vapor lamp, which emits powerful ultraviolet light energy. Vital genetic components contained in microorganisms absorb the light energy. This process disrupts the DNA and prevents reproduction which ultimately destroys the organism.

3. The now treated water then exits through the outlet port of the chamber and is ready for consumption.

Optional Accessories



254M UV Monitor

254M UV Monitor - UV dosage metering device. This true UV Monitor reads only the 254-nm intensity output of the ultraviolet light within the UV treatment chamber.



Solenoid

Solenoid - Optional fail safe shut-off valve.

