




The *WTA Ultraviolet, TRI Series*, is an effective way to provide safe, bacteria free water for your home or office, 24 hours a day, 7 days a week. WTA's Ultraviolet Disinfection Systems are setting the standards for water disinfection requirements in the water treatment industry.

OPTIONAL ACCESSORIES



Solenoid:

This solenoid acts as a fail safe shut-off valve. Providing extra protection for the system.



Monitor:

UV dosage metering device. This true UV Monitor reads only the 254-nm intensity output of the Ultraviolet Light within the UV treatment chamber. Optional on all Triton Units

All ATS Units are
Proudly Made:
in the
U.S.A.



and meets
WQA standards



FEATURES:

- Standard Warranty
- LED Visual & Audible Alarms
- 30 Day Replacement Alarm & Countdown Timer
- Lamp Life Expired Alarm
- UV Lamp Out Alarm
- 365 Day Resettable Lamp Life Counter
- Flow Control
- Solenoid Valve Connection
- Site Port
- Built in Surge Protector and Fuse

BENEFITS:

- No taste or odor
- Eliminates microbiological contaminants without chemicals
- Bacteria, viruses and other organisms are destroyed safely inside a factory sealed and tested stainless steel chamber.

SPECIFICATIONS:

| Model# | Max. Flow GPM | No. Lamps | KW @ 120V | AMP @ 120V | Pipe Size | Overall Dimensions L x W x D | Wetted Material | Shipping Weight |
|----------|------------------|--------------|--------------|---------------|--------------|---------------------------------|--------------------|--------------------|
| TRI - 8 | 8 | 1 | 0.03 | 0.25 | 3/4" MIP | 21" x 3.5" x 3.5" | 304 SS | 9 lbs. |
| TRI - 12 | 12 | 1 | 0.03 | 0.25 | 3/4" MIP | 32" x 3.5" x 3.5" | 304 SS | 18 lbs. |
| TRI - 20 | 20 | 1 | 0.03 | 0.25 | 1" MIP | 35" x 5" x 5" | 304 SS | 21 lbs. |

NOTES: 220V Specs are available upon request

TRITON Series UV DISINFECTION

Parts Breakdown:

1. Mounting Bracket
2. Outlet
3. Site Port
4. Quartz Sleeve
5. UV Lamp
6. Inlet
7. Quartz Sleeve Stabilizer
8. Optional Bottom Mounting Bracket

